

Application: Indoor; Outdoor;

Installation Type: Fixed; Rental;

Certificate: CE; RoHS; ETL; FCC;

Panel Photo



R0.9 SPECIFICATIONS

Version: V20210706

	Parameter	Value	Unit
Module	Pixel Pitch	0.93	mm
	LED Type	COB 3in1	/
	Module Size(WxH)	300x337.5	mm
	Pixel Per Module	320x360	Dots
	Module Weight	1.4	Kg
Panel	Size(WxHxT)	600x337.5x59.5mm	mm
	Pixels	640x360	dots
	Material	Die casting aluminum	/
	Weight	6.5	Kg
	Brightness	450	nit
	Processing depth	13	bit
	Display refresh rate	3000	Hz
	Color Temperature	3200~9300	K
	Viewing angle(H)	170 (-85 / +85)	deg.
	Viewing angle(V)	160 (-80/+80)	deg.
Application	AC Operating Voltage	100~240	V
	AC Input Frequency	50/ 60	Hz
	Power Consumption (Max./Avg.)	450/150	W/m ²
	Storage Temperature	- 40~ + 60	°C
	Operating Temperature	- 10~ + 40	°C
	Storage Humidity	10 % ~90 %	RH
	Operating Humidity	10 % ~90 %	RH
	IP Rating (Front/Rear)	IP30/IP30	/
	Module Maintenance	Front	/
	PSU & Others Maintenance	Front	/
	Panel Installation Type	Front Installation	/

Remark: Power consumption tolerance: $\pm 15\%$, according to the actual situation.